

Specification for Approval

Customer:

Customer P/N:

EEC P/N:

LT-4532B-121MMN

Spec No.:

Version No.:

V0.1

Description:

Pulse Transformer

10G Base-T Available

Customer Approval		EEC Approval	
Inspected By:		Issued By:	Fuming Chen
Checked By:		Checked By:	/
Approved By:		Approved By:	Jerry Gu
Approved Date:		Issued Date:	2025/7/24

Please Return One Copy to Us After Approved,TKS! (承认后请回寄一份,谢谢)

Remark:

1. Before use, please confirm whether this product is suitable for your design, Scientific only ensure products meet this specification.
2. This specification data change must be confirmed by both parties,any individual modification is invalid.
3. If customer placed orders without signing back this specification, it is regarded as recognition.



绵阳敦源电子科技有限公司

Mianyang Dunyuan Electronics Technology Co.,Ltd

地址：四川省绵阳市高新区综合保税区

ADD: Comprehensive Bonded Zone, High-Tech Industrial Development Zone Mianyang, SiChuan

[illegible]


DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
Pulse Transformer	LT-4532B-121MMN		PAGE: 1/6



Specification for Approval

1 Features And Benefits


- LAN interfaces of various devices including network devices, communication equipment, digital consumer electronics, etc
- Compliant With Ethernet 10GBase-T
- Improved Return Loss And Cross Talk Properties
- High-Quality Product That Uses Auto Winding
- Operating temperature -40°C to +105°C
- 1500Vrms/1mA/60s Hi-pot Support
- RoHS Compliant



2 Electrical Specifications @ 25°C


10G Base-T												
Part Number	OCL (μ H)	DCR (Ω)	Insertion Loss (dB)				Return Loss (dB)					PoE Rating
	Min	Max	Max				Min					
	100KHz,0.1V		1-200 MHz	200- 300 MHz	300- 400 MHz	400- 500 MHz	1-100 MHz	100- 200 MHz	200- 300 MHz	300- 400 MHz	400- 500 MHz	
LT-4532B-121MMN	120 @15mA	2.00	-1.2	-1.5	-2	-3	-18	-16	-12	-10	-8	NON POE

3 Dimensions (mm)& recommend layout




DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
Pulse Transfomer	LT-4532B-121MMN		PAGE: 2/6

4 Schematics






5 Recommended Reflow Profile




DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
Pulse Transformer	LT-4532B-121MMN		PAGE: 3/6


6 Packaging specification




Four Reel



One Inner Carton



Five Inner Carton



One Export Carton

Package Quantity:
 One Reel=2000 Pcs
 One Inner Carton=2000*4=8000 Pcs
 One Export Carton=8000*5=40000 Pcs

DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
Pulse Transformer	LT-4532B-121MMN		PAGE: 4/6

7 Reliability test

NO.	Test Item	Standard Reference	Test Condition
1	High temperature storage test	IPC/JEDEC J-STD-020D	Temperature: 125±2℃ Time: 168 hours Measurement at 24±4 hours after test conclusion.
2	Low temperature test	IPC/JEDEC J-STD-020D	Temperature: -40±2℃ Time: 168 hours Measurement at 24±4 hours after test conclusion.
3	Constant temperature and constant humidity test	GB/T 2423.3 (IEC 60068-2-78)	Temperature: 40±2℃ / humidity:93±2%RH Time: 168 hours Measurement at 24±4 hours after test conclusion.
4	High temperature and high humidity test	GB/T 2423.50	Temperature: 85±2℃ / humidity:85±2%RH Time: 168 hours Measurement at 24±4 hours after test conclusion.
5	Thermal shock test	IPC/JEDEC J-STD-020D	First -40±5℃ for 30±2 minutes, last 125℃ 30±2 minutes as 1 cycle. Total 100 cycles.
6	Salt spray test	GB/T2423.17 (IEC 60068-2-11)	Concentration : (5±0.1) % PH : 6.5 ~ 7.2 Temperature: 35 ± 2 ℃ Time: 24 hours
7	Solder ability test	GB/T 2423.28 (IEC 60068-2-20)	Preheating: 150±5℃, 60 seconds Immerse the terminal in flux for 5 seconds, then dip the terminal into a soldering bath of 245±5℃ for 2±0.5 seconds.
8	Drop test	GB/T 2423.8 (IEC 60068-2-32)	Floor should be hard, strong, concrete. Height: 0.8m. Test 6 surfaces, 3 ridges and 1 corner of Test-box.
9	Vibration test	GB/T 4857.7	Apply frequency 10~100~10Hz 1.52mm±10% amplitude in each of perpendicular direction for 20 minutes. Total 12 cycles
10	Soldering resistance test	GB/T 2423.50	Preheating: 150±5℃, 60~120 seconds dip the terminal into a soldering bath of 260±5℃ for 10±3 seconds with 3 times.
11	Terminal strength	MIL-STD-202	PCB specification: 100mm X 40mm. 4 layer board Thickness: 1.60 + / - 0.2 mm 1、>0805 inch/2012mm : 9.8N (1kg) 2、<=0805 inch/2012mm: 4.9N (0.5kg) Hold time: 60±1 s
12	Plate bending test	MIL-STD-202	PCB specification: 100mm X 40mm. 4 layer board Thickness: 1.60 + / - 0.2 mm Displacement: 2mm Hold time: 60±1s

DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
Pulse Transformer	LT-4532B-121MMN		PAGE: 5/6



REMINDERS

- The best assembly quality guarantee period of product: 12 months (From shipment date)
Storage condition : seal in packaging, (temperature: 5 to 40°C, humidity: 10 to 75% RH or less).
- If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of electrodes and affect soldering status.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Always handle products with care to avoid damage.
- Do not touch electrodes with bare hands directly, as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications. If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- Do not use for Automotive application.

DESCRIPTION	EEC P/N	SPEC NO.:	VERSION NO.: V0.1
Pulse Transformer	LT-4532B-121MMN		PAGE: 6/6