

Specification for Approval

Customer: _____

Customer P/N: _____

EEC P/N: SH16503N0

Spec No.: _____

Version No.: V0.1

Description: 10/100 BASE-TX

Laser Marking

Customer Approval		EEC Approval	
Inspected By:		Issued By:	Xingyu,He
Checked By:		Checked By:	Bob
Approved By:		Approved By:	Jerry
Approved Date:		Issued Date:	2024/7/5

Please Return One Copy to Us After Approved,TKS! (承认后请回寄一份,谢谢)

- Remark:
- 1. Before use, please confirm whether this product is suitable for your design, Scientific only ensure products meet this specification.
 - 2. This specification data change must be confirmed by both parties,any individual modification is invalid.
 - 3. If customer placed orders without signing back this specification, it is regarded as recognition.





绵阳敦源电子科技有限公司
Mianyang Dunyuan Electronics Technology Co.,Ltd
地址：四川省绵阳市高新区综合保税区
ADD: Comprehensive Bonded Zone, High-Tech Industrial Development Zone Mianyang, SiChuan



[illegible]

DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
10/100 BASE-TX	SH16503N0		PAGE: 1/4


A. MECHANICAL(unit:mm)



Suggested PAD Layout



B. Schematics




DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
10/100 BASE-TX	SH16503N0		PAGE: 2/4

C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C

1. OCL: 350uH Min @ 100 KHz, 0.1V with 8mA DC BIAS
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: 1400mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -1.1 dB Max @ 1-100 MHz
6. Return Loss: -18 dB Min @ 1-30 MHz
-14.4 dB Min @ 40 MHz
-13.1 dB Min @ 50 MHz
-12 dB Min @ 60-80 MHz
7. Cross Talk: -30 dB Min @ 1-100 MHz
8. Common Mode Rejection: -30 dB Min @ 1-100 MHz
9. Isolation Hipot: 1500VAC 1mA 60S
10. Operating temperature 0°C to +70°C
11. Storage temperature -40°C to +85°C

D. RECOMMEND WAVE SOLDERING CURVE

MSL:

Grade: 1 level. Floor life: 0.5 year Condition: $\leq 30^\circ C/60\%RH$.




Ramp up rate=3°C/s max Ramp down rate=6°C/s max

$T_L=217^\circ C$ $t_L=60s-150s$ $T_p=250\pm 3^\circ C$ Time within 5°C of actual Peak Temperature (t_p): 20~40s


$T_{s\ min}=150^\circ C$ $T_{s\ max}=200^\circ C$ $T_{s\ min}$ to $T_{s\ max}$: 60s-180s, 25°C to peak Temperature: 8minutes max

DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
10/100 BASE-TX	SH16503N0		PAGE: 3/4


E. Packaging specification




Three Reel



Inner Carton



Two Inner Carton



Export Carton

Package Quantity:

One Reel=600Pcs

One Inner Carton=600*3=1800Pcs

One Export Carton=1800*2=3600Pcs

DESCRIPTION	EEC P/N:	SPEC NO	Version No.: V0.1
10/100 BASE-TX	SH16503N0		PAGE: 4/4